

## PSE301G

### 30W POE Injector, Gigabit

#### FEATURES

- 30W output power
- Data rate: 10/100/1000Mbps
- Full protection for OCP, OLP and OVP
- LED indication for power and POE status



#### OVERVIEW

The PSE301G is an economical high power POE Injector that feeds power (30W Max.) to powered devices (PD), such as wireless Access Points (APs), IP cameras, IP phones, Thin Computers, Printers, or Network Attached Storage (NAS) by Cat5e or Cat6 network cables. With an internal power supply, the PSE301G accepts full range of AC Power (100-240V) into low voltage and delivers power up to 30W and 100 meters distance.

# PSE301G

## SPECIFICATIONS

Input	100-240VAC 50/60Hz
Output	30W(Max)
Power + Data Out	4/5(+)&7/8(-) for Power
Data In	Connects PC/HUB/Switch
Weight	0.35Kg
Dimensions	146(L) x 64(W) x 42(T) mm
Data rate	10/100 M bit/s
Ethernet Cable	TIA/EIA 568B Cat.5e or Cat.6
Connector	RJ-45
Operating Temperature	0°C~40°C
Storage Temperature	-10°C~70°C
Operating Humidity	5%~90%RH
LED	AC Power on, Ethernet status
Certification	CE, FCC

## ORDERING INFORMATION

PSE301GA	30W POE Injector, Gigabit, US Type
PSE301GB	30W POE Injector, Gigabit, EURO Type
PSE301GC	30W POE Injector, Gigabit, UK Type